

Network Working Group
Request for Comments: 4070
Category: Standards Track

M. Dodge
ECI Telecom
B. Ray
PESA Switching Systems
May 2005

Definitions of Managed Object Extensions
for Very High Speed Digital Subscriber Lines (VDSL) Using
Multiple Carrier Modulation (MCM) Line Coding

Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This document defines a portion of the Management Information Base (MIB) module for use with network management protocols in the Internet community. In particular, it describes objects used for managing the Line Code Specific parameters of Very High Speed Digital Subscriber Line (VDSL) interfaces using Multiple Carrier Modulation (MCM) Line Coding. It is an optional extension to the VDSL-LINE-MIB, RFC 3728, which handles line code independent objects.

Table of Contents

1. The Internet-Standard Management Framework	2
2. Overview	2
2.1. Relationship of this MIB Module to other MIB Modules	3
2.2. Conventions used in the MIB Module	3
2.3. Structure	3
2.4. Persistence	4
3. Conformance and Compliance	5
4. Definitions	5
5. Acknowledgments	19
6. Security Considerations	19
7. IANA Considerations	21
8. References	21
8.1. Normative References	21
8.2. Informative References	23

1. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

2. Overview

This document describes an SNMP MIB module for managing the Line Code Dependent, Physical Medium Dependent (PMD), Layer of MCM VDSL Lines. These definitions are based upon the specifications for VDSL as defined in T1E1, European Telecommunications Standards Institute (ETSI), and International Telecommunication Union (ITU) documentation [T1E1311, T1E1011, T1E1013, ETSI2701, ETSI2702, ITU9931, ITU9971]. Additionally the protocol-dependent (and line-code dependent) management framework for VDSL lines specified by the Digital Subscriber Line Forum (DSLIF) has been taken into consideration [DSLIFTR57].

The MIB module is located in the MIB tree under MIB-2 transmission.

The key words "MUST", "MUST NOT", "RECOMMENDED", and "SHOULD" in this document are to be interpreted as described in [RFC2119].

2.1. Relationship of this MIB Module to other MIB Modules

The relationship of the VDSL Line MIB module to other MIB modules and in particular to the IF-MIB, as presented in RFC 2863 [RFC2863], is discussed in the VDSL-LINE-MIB, RFC 3728 [RFC3728]. This section outlines the relationship of this VDSL Line Extension MIB to the VDSL-LINE-MIB, RFC 3728 [RFC3728].

2.2. Conventions used in the MIB Module

2.2.1. Naming Conventions

- A. Vtuc -- (VTUC) transceiver at near (Central) end of line
- B. Vtur -- (VTUR) transceiver at Remote end of line
- C. Vtu -- One of either Vtuc or Vtur
- D. Curr -- Current
- E. LCS -- Line Code Specific
- F. Max -- Maximum
- G. PSD -- Power Spectral Density
- H. Rx -- Receive
- I. Tx -- Transmit

2.3. Structure

The MCM VDSL Line Extension MIB contains the following MIB group:

- o vdslMCMGroup :

This group supports MIB objects for defining configuration profiles and for monitoring individual bands of Multiple Carrier Modulation (MCM) VDSL modems. It contains the following tables:

- vdslLineMCMConfProfileTable
- vdslLineMCMConfProfileTxBandTable
- vdslLineMCMConfProfileRxBandTable
- vdslLineMCMConfProfileTxPSDTable
- vdslLineMCMConfProfileMaxTxPSDTable
- vdslLineMCMConfProfileMaxRxPSDTable

If the MCM VDSL Line Extension MIB is implemented then all of the objects in this group MUST be implemented.

Figure 1, below, displays the relationship of the tables in the vdslMCMGroup to the vdslGroup and to the ifEntry:

```

ifEntry(ifType=97) ----> vdslLineTableEntry 1:(0..1)

vdslLineTableEntry (vdslLineCoding=MCM)

vdslLineConfProfileEntry(vdslLineConfProfileName)
    ----> vdslLineMCMConfProfileTable 1:(0..1)
    ----> vdslLineMCMConfProfileTxBandTable 1:(0..n)
    ----> vdslLineMCMConfProfileRxBandTable 1:(0..n)
    ----> vdslLineMCMConfProfileTxPSDTable 1:(0..n)
    ----> vdslLineMCMConfProfileMaxTxPSDTable 1:(0..n)
    ----> vdslLineMCMConfProfileMaxRxPSDTable 1:(0..n)

```

Figure 1: Table Relationships

When the object vdslLineCoding is set to MCM, vdslLineConfProfileName is used as the index to each of the six vdslLineMCMConfProfile Tables. The existence of an entry in any of the tables of the vdslMCMGroup is optional.

2.4. Persistence

All read-create objects defined in this MIB module SHOULD be stored persistently. Following is an exhaustive list of these persistent objects:

```

vdslMCMConfProfileTxWindowLength
vdslMCMConfProfileRowStatus
vdslMCMConfProfileTxBandNumber
vdslMCMConfProfileTxBandStart
vdslMCMConfProfileTxBandStop
vdslMCMConfProfileTxBandRowStatus
vdslMCMConfProfileRxBandStart
vdslMCMConfProfileRxBandStop
vdslMCMConfProfileRxBandRowStatus
vdslMCMConfProfileTxPSDTone
vdslMCMConfProfileTxPSDPSD
vdslMCMConfProfileTxPSDRowStatus
vdslMCMConfProfileMaxTxPSDTone
vdslMCMConfProfileMaxTxPSDPSD
vdslMCMConfProfileMaxTxPSDRowStatus
vdslMCMConfProfileMaxRxPSDTone
vdslMCMConfProfileMaxRxPSDPSD
vdslMCMConfProfileMaxRxPSDRowStatus

```

Note also that the interface indices in this MIB are maintained persistently. View-based Access Control Model (VACM) data relating to these SHOULD be stored persistently as well [RFC3415].

3. Conformance and Compliance

An MCM based VDSL agent does not have to implement this MIB to be compliant with RFC 3728 [RFC3728]. If the MCM VDSL Line Extension MIB is implemented then the following group is mandatory:

- vdslMCMGroup

4. Definitions

VDSL-LINE-EXT-MCM-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY,
OBJECT-TYPE,
transmission,

Unsigned32	FROM SNMPv2-SMI	-- [RFC2578]
RowStatus	FROM SNMPv2-TC	-- [RFC2579]
MODULE-COMPLIANCE,		
OBJECT-GROUP	FROM SNMPv2-CONF	-- [RFC2580]
vdslLineConfProfileName	FROM VDSL-LINE-MIB;	-- [RFC3728]

vdslExtMCM MIB MODULE-IDENTITY

LAST-UPDATED "200504280000Z" -- April 28, 2005

ORGANIZATION "ADSLMIB Working Group"

CONTACT-INFO "WG-email: adslmib@ietf.org

Info: <https://www1.ietf.org/mailman/listinfo/adslmib>

Chair: Mike Sneed
Sand Channel Systems

Postal: P.O. Box 37324
Raleigh NC 27627-732

Email: sneedmike@hotmail.com

Phone: +1 206 600 7022

Co-Chair/Co-editor:

Bob Ray
PESA Switching Systems, Inc.

Postal: 330-A Wynn Drive
Huntsville, AL 35805

USA

Email: rray@pesa.com

Phone: +1 256 726 9200 ext. 142

Co-editor: Menachem Dodge
 ECI Telecom Ltd.
 Postal: 30 hasivim St.
 Petach Tikva 49517,
 Israel.
 Email: mbdodge@ieee.org
 Phone: +972 3 926 8421

"

DESCRIPTION

"The VDSL-LINE-MIB found in RFC 3728 defines objects for the management of a pair of VDSL transceivers at each end of the VDSL line. The VDSL-LINE-MIB configures and monitors the line code independent parameters (TC layer) of the VDSL line. This MIB module is an optional extension of the VDSL-LINE-MIB and defines objects for configuration and monitoring of the line code specific (LCS) elements (PMD layer) for VDSL lines using MCM coding. The objects in this extension MIB MUST NOT be used for VDSL lines using Single Carrier Modulation (SCM) line coding. If an object in this extension MIB is referenced by a line which does not use MCM, it has no effect on the operation of that line.

Naming Conventions:

Vtuc -- (VTUC) transceiver at near (Central) end of line
 Vtur -- (VTUR) transceiver at Remote end of line
 Vtu -- One of either Vtuc or Vtur
 Curr -- Current
 LCS -- Line Code Specific
 Max -- Maximum
 PSD -- Power Spectral Density
 Rx -- Receive
 Tx -- Transmit

Copyright (C) The Internet Society (2005). This version of this MIB module is part of RFC 4070: see the RFC itself for full legal notices."

REVISION "200504280000Z" -- April 28, 2005

DESCRIPTION "Initial version, published as RFC 4070."

::= { transmission 229 }

vdslLineExtMCMMib OBJECT IDENTIFIER ::= { vdsExtMCMMIB 1 }
 vdsLineExtMCMMibObjects OBJECT IDENTIFIER ::= { vdsLineExtMCMMib 1 }

--

-- Multiple carrier modulation (MCM) configuration profile tables

--

vdsLineMCMConfProfileTable OBJECT-TYPE

SYNTAX SEQUENCE OF VdsLineMCMConfProfileEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains additional information on multiple carrier VDSL lines. One entry in this table reflects a profile defined by a manager which can be used to configure the VDSL line.

If an entry in this table is referenced by a line which does not use MCM, it has no effect on the operation of that line.

All read-create-objects defined in this table SHOULD be stored persistently."

```
::= { vdsLineExtMCMmibObjects 1 }
```

vdsLineMCMConfProfileEntry OBJECT-TYPE

SYNTAX VdsLineMCMConfProfileEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry consists of a list of parameters that represents the configuration of a multiple carrier modulation VDSL modem."

INDEX { vdsLineConfProfileName }

```
::= { vdsLineMCMConfProfileTable 1 }
```

VdsLineMCMConfProfileEntry ::=

SEQUENCE

```
{
    vdsLineMCMConfProfileTxWindowLength      Unsigned32,
    vdsLineMCMConfProfileRowStatus           RowStatus
}
```

vdsLineMCMConfProfileTxWindowLength OBJECT-TYPE

SYNTAX Unsigned32 (1..255)

UNITS "samples"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Specifies the length of the transmit window, counted in samples at the sampling rate corresponding to the negotiated value of N."

REFERENCE "T1E1.4/2000-013R4" -- Part 3, MCM

```
::= { vdsLineMCMConfProfileEntry 1 }
```

vdsLineMCMConfProfileRowStatus OBJECT-TYPE

SYNTAX RowStatus
 MAX-ACCESS read-create
 STATUS current

DESCRIPTION

"This object is used to create a new row or modify or delete an existing row in this table.

A profile is activated by setting this object to 'active'. When 'active' is set, the system will validate the profile.

None of the columns in this row may be modified while the row is in the 'active' state.

Before a profile can be deleted or taken out of service, (by setting this object to 'destroy' or 'notInService') it must first be unreferenced from all associated lines."

::= { vdsLineMCMConfProfileEntry 2 }

vdsLineMCMConfProfileTxBandTable OBJECT-TYPE

SYNTAX SEQUENCE OF VdsLineMCMConfProfileTxBandEntry
 MAX-ACCESS not-accessible
 STATUS current

DESCRIPTION

"This table contains transmit band descriptor configuration information for a VDSL line. Each entry in this table reflects the configuration for one of possibly many bands with a multiple carrier modulation (MCM) VDSL line. These entries are defined by a manager and can be used to configure the VDSL line.

If an entry in this table is referenced by a line which does not use MCM, it has no effect on the operation of that line.

All read-create-objects defined in this table SHOULD be stored persistently."

::= { vdsLineExtMCMObjects 2 }

vdsLineMCMConfProfileTxBandEntry OBJECT-TYPE

SYNTAX VdsLineMCMConfProfileTxBandEntry
 MAX-ACCESS not-accessible
 STATUS current

DESCRIPTION

"Each entry consists of a transmit band descriptor, which is defined by a start and a stop tone index."

INDEX { vdsLineConfProfileName,


```

        vdslLineMCMConfProfileTxBandNumber }
 ::= { vdslLineMCMConfProfileTxBandTable 1 }

VdslLineMCMConfProfileTxBandEntry ::=
    SEQUENCE
    {
        vdslLineMCMConfProfileTxBandNumber          Unsigned32,
        vdslLineMCMConfProfileTxBandStart            Unsigned32,
        vdslLineMCMConfProfileTxBandStop             Unsigned32,
        vdslLineMCMConfProfileTxBandRowStatus        RowStatus
    }

vdslLineMCMConfProfileTxBandNumber OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4096)
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "The index for this band descriptor entry."
    ::= { vdslLineMCMConfProfileTxBandEntry 1 }

vdslLineMCMConfProfileTxBandStart OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4096)
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "Start tone index for this band."
    REFERENCE    "T1E1.4/2000-013R4"      -- Part 3, MCM
    ::= { vdslLineMCMConfProfileTxBandEntry 2 }

vdslLineMCMConfProfileTxBandStop OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4096)
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "Stop tone index for this band."
    REFERENCE    "T1E1.4/2000-013R4"      -- Part 3, MCM
    ::= { vdslLineMCMConfProfileTxBandEntry 3 }

vdslLineMCMConfProfileTxBandRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "This object is used to create a new row or modify or
        delete an existing row in this table.
        A profile is activated by setting this object to 'active'.
        When 'active' is set, the system will validate the profile."

```

Each entry must be internally consistent, the Stop Tone must be greater than the Start Tone. Each entry must also be externally consistent, all entries indexed by a specific profile must not overlap. Validation of the profile will check both internal and external consistency.

None of the columns in this row may be modified while the row is in the 'active' state.

Before a profile can be deleted or taken out of service, (by setting this object to 'destroy' or 'notInService') it must be first unreferenced from all associated lines."

```
::= { vdslLineMCMConfProfileTxBandEntry 4 }
```

vdslLineMCMConfProfileRxBandTable OBJECT-TYPE

SYNTAX SEQUENCE OF VdslLineMCMConfProfileRxBandEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains receive band descriptor configuration information for a VDSL line. Each entry in this table reflects the configuration for one of possibly many bands with a multiple carrier modulation (MCM) VDSL line. These entries are defined by a manager and can be used to configure the VDSL line.

If an entry in this table is referenced by a line which does not use MCM, it has no effect on the operation of that line.

All read-create-objects defined in this table SHOULD be stored persistently."

```
::= { vdslLineExtMCMObjects 3 }
```

vdslLineMCMConfProfileRxBandEntry OBJECT-TYPE

SYNTAX VdslLineMCMConfProfileRxBandEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry consists of a transmit band descriptor, which is defined by a start and a stop tone index."

```
INDEX { vdslLineConfProfileName,
        vdslLineMCMConfProfileRxBandNumber }
```

```
::= { vdslLineMCMConfProfileRxBandTable 1 }
```

VdslLineMCMConfProfileRxBandEntry ::=

SEQUENCE

{	
vdsLineMCMConfProfileRxBandNumber	Unsigned32,
vdsLineMCMConfProfileRxBandStart	Unsigned32,
vdsLineMCMConfProfileRxBandStop	Unsigned32,
vdsLineMCMConfProfileRxBandRowStatus	RowStatus
}	

vdsLineMCMConfProfileRxBandNumber OBJECT-TYPE

SYNTAX Unsigned32 (1..4096)
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "The index for this band descriptor entry."
 ::= { vdsLineMCMConfProfileRxBandEntry 1 }

vdsLineMCMConfProfileRxBandStart OBJECT-TYPE

SYNTAX Unsigned32 (1..4096)
 MAX-ACCESS read-create
 STATUS current
 DESCRIPTION
 "Start tone index for this band."
 REFERENCE "T1E1.4/2000-013R4" -- Part 3, MCM
 ::= { vdsLineMCMConfProfileRxBandEntry 2 }

vdsLineMCMConfProfileRxBandStop OBJECT-TYPE

SYNTAX Unsigned32 (1..4096)
 MAX-ACCESS read-create
 STATUS current
 DESCRIPTION
 "Stop tone index for this band."
 REFERENCE "T1E1.4/2000-013R4" -- Part 3, MCM
 ::= { vdsLineMCMConfProfileRxBandEntry 3 }

vdsLineMCMConfProfileRxBandRowStatus OBJECT-TYPE

SYNTAX RowStatus
 MAX-ACCESS read-create
 STATUS current
 DESCRIPTION
 "This object is used to create a new row or modify or
 delete an existing row in this table.

A profile is activated by setting this object to 'active'.
 When 'active' is set, the system will validate the profile.
 Each entry must be internally consistent, the Stop Tone must
 be greater than the Start Tone. Each entry must also be
 externally consistent, all entries indexed by a specific

profile must not overlap. Validation of the profile will check both internal and external consistency.

None of the columns in this row may be modified while the row is in the 'active' state.

Before a profile can be deleted or taken out of service, (by setting this object to 'destroy' or 'notInService') it must be first unreferenced from all associated lines."

```
::= { vdslLineMCMConfProfileRxBandEntry 4 }
```

vdslLineMCMConfProfileTxPSDTable OBJECT-TYPE

SYNTAX SEQUENCE OF VdslLineMCMConfProfileTxPSDEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains transmit PSD mask descriptor configuration information for a VDSL line. Each entry in this table reflects the configuration for one tone within a multiple carrier modulation (MCM) VDSL line. These entries are defined by a manager and can be used to configure the VDSL line.

If an entry in this table is referenced by a line which does not use MCM, it has no effect on the operation of that line.

All read-create-objects defined in this table SHOULD be stored persistently."

```
::= { vdslLineExtMCMmibObjects 4 }
```

vdslLineMCMConfProfileTxPSDEntry OBJECT-TYPE

SYNTAX VdslLineMCMConfProfileTxPSDEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry consists of a transmit PSD mask descriptor, which defines the power spectral density (PSD) for a tone."

```
INDEX { vdslLineConfProfileName,
        vdslLineMCMConfProfileTxPSDNumber }
```

```
::= { vdslLineMCMConfProfileTxPSDTable 1 }
```

VdslLineMCMConfProfileTxPSDEntry ::=

SEQUENCE

```
{
    vdslLineMCMConfProfileTxPSDNumber          Unsigned32,
```

vdsLineMCMConfProfileTxPSDTone	Unsigned32,
vdsLineMCMConfProfileTxPSDPSD	Unsigned32,
vdsLineMCMConfProfileTxPSDRowStatus	RowStatus
}	

vdsLineMCMConfProfileTxPSDNumber OBJECT-TYPE

SYNTAX Unsigned32 (1..4096)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The index for this mask descriptor entry."

::= { vdsLineMCMConfProfileTxPSDEntry 1 }

vdsLineMCMConfProfileTxPSDTone OBJECT-TYPE

SYNTAX Unsigned32 (1..4096)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The tone index for which the PSD is being specified."

REFERENCE "T1E1.4/2000-013R4" -- Part 3, MCM

::= { vdsLineMCMConfProfileTxPSDEntry 2 }

vdsLineMCMConfProfileTxPSDPSD OBJECT-TYPE

SYNTAX Unsigned32

UNITS "0.5dBm/Hz"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Power Spectral Density level in steps of 0.5dBm/Hz with an offset of -140dBm/Hz."

REFERENCE "T1E1.4/2000-013R4" -- Part 3, MCM

::= { vdsLineMCMConfProfileTxPSDEntry 3 }

vdsLineMCMConfProfileTxPSDRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object is used to create a new row or modify or delete an existing row in this table."

A profile is activated by setting this object to 'active'. When 'active' is set, the system will validate the profile.

None of the columns in this row may be modified while the row is in the 'active' state.

Before a profile can be deleted or taken out of

service, (by setting this object to 'destroy' or 'notInService') it must be first unreferenced from all associated lines."

```
::= { vdslLineMCMConfProfileTxPSDEntry 4 }
```

vdslLineMCMConfProfileMaxTxPSDTable OBJECT-TYPE

SYNTAX SEQUENCE OF VdslLineMCMConfProfileMaxTxPSDEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains transmit maximum PSD mask descriptor configuration information for a VDSL line. Each entry in this table reflects the configuration for one tone within a multiple carrier modulation (MCM) VDSL modem. These entries are defined by a manager and can be used to configure the VDSL line.

If an entry in this table is referenced by a line which does not use MCM, it has no effect on the operation of that line.

All read-create-objects defined in this table SHOULD be stored persistently."

```
::= { vdslLineExtMCMmibObjects 5 }
```

vdslLineMCMConfProfileMaxTxPSDEntry OBJECT-TYPE

SYNTAX VdslLineMCMConfProfileMaxTxPSDEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry consists of a transmit PSD mask descriptor, which defines the maximum power spectral density (PSD) for a tone."

INDEX { vdslLineConfProfileName,
vdslLineMCMConfProfileMaxTxPSDNumber }

```
::= { vdslLineMCMConfProfileMaxTxPSDTable 1 }
```

VdslLineMCMConfProfileMaxTxPSDEntry ::=

SEQUENCE

{	
vdslLineMCMConfProfileMaxTxPSDNumber	Unsigned32,
vdslLineMCMConfProfileMaxTxPSDTone	Unsigned32,
vdslLineMCMConfProfileMaxTxPSDPSD	Unsigned32,
vdslLineMCMConfProfileMaxTxPSDRowStatus	RowStatus
}	

vdslLineMCMConfProfileMaxTxPSDNumber OBJECT-TYPE

SYNTAX Unsigned32 (1..4096)

```

MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION
    "The index for this band descriptor entry."
 ::= { vdslLineMCMConfProfileMaxTxPSDEntry 1 }

```

vdslLineMCMConfProfileMaxTxPSDTone OBJECT-TYPE

```

SYNTAX        Unsigned32 (1..4096)
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
    "The tone index for which the PSD is being specified.
     There must not be multiple rows defined, for a particular
     profile, with the same value for this field."
REFERENCE     "T1E1.4/2000-013R4"      -- Part 3, MCM
 ::= { vdslLineMCMConfProfileMaxTxPSDEntry 2 }

```

vdslLineMCMConfProfileMaxTxPSDPSD OBJECT-TYPE

```

SYNTAX        Unsigned32
UNITS         "0.5dBm/Hz"
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
    "Power Spectral Density level in steps of 0.5dBm/Hz with
     an offset of -140dBm/Hz."
REFERENCE     "T1E1.4/2000-013R4"      -- Part 3, MCM
 ::= { vdslLineMCMConfProfileMaxTxPSDEntry 3 }

```

vdslLineMCMConfProfileMaxTxPSDRowStatus OBJECT-TYPE

```

SYNTAX        RowStatus
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
    "This object is used to create a new row or modify or
     delete an existing row in this table.
     A profile is activated by setting this object to 'active'.
     When 'active' is set, the system will validate the profile.
     There must be only one entry in this table for each tone
     associated with a specific profile. This will be checked
     during the validation process.

```

None of the columns in this row may be modified while the row is in the 'active' state.

Before a profile can be deleted or taken out of service, (by setting this object to 'destroy' or 'notInService') it must be first unreferenced from all associated lines."

```
::= { vdslLineMCMConfProfileMaxTxPSDEntry 4 }
```

```
vdslLineMCMConfProfileMaxRxPSDTable OBJECT-TYPE
```

```
SYNTAX          SEQUENCE OF VdslLineMCMConfProfileMaxRxPSDEntry
```

```
MAX-ACCESS      not-accessible
```

```
STATUS          current
```

```
DESCRIPTION
```

"This table contains maximum receive PSD mask descriptor configuration information for a VDSL line. Each entry in this table reflects the configuration for one tone within a multiple carrier modulation (MCM) VDSL modem. These entries are defined by a manager and can be used to configure the VDSL line.

If an entry in this table is referenced by a line which does not use MCM, it has no effect on the operation of that line.

All read-create-objects defined in this table SHOULD be stored persistently."

```
::= { vdslLineExtMCMObjects 6 }
```

```
vdslLineMCMConfProfileMaxRxPSDEntry OBJECT-TYPE
```

```
SYNTAX          VdslLineMCMConfProfileMaxRxPSDEntry
```

```
MAX-ACCESS      not-accessible
```

```
STATUS          current
```

```
DESCRIPTION
```

"Each entry consists of a transmit PSD mask descriptor, which defines the power spectral density (PSD) for a tone."

```
INDEX { vdslLineConfProfileName,
        vdslLineMCMConfProfileMaxRxPSDNumber }
```

```
::= { vdslLineMCMConfProfileMaxRxPSDTable 1 }
```

```
VdslLineMCMConfProfileMaxRxPSDEntry ::=
```

```
SEQUENCE
```

```
{
    vdslLineMCMConfProfileMaxRxPSDNumber          Unsigned32,
    vdslLineMCMConfProfileMaxRxPSDTone            Unsigned32,
    vdslLineMCMConfProfileMaxRxPSDPSD             Unsigned32,
    vdslLineMCMConfProfileMaxRxPSDRowStatus       RowStatus
}
```

```
vdslLineMCMConfProfileMaxRxPSDNumber OBJECT-TYPE
```

```
SYNTAX          Unsigned32 (1..4096)
```

```
MAX-ACCESS      not-accessible
```

```
STATUS          current
```


DESCRIPTION

"The index for this band descriptor entry."
 ::= { vdslLineMCMConfProfileMaxRxPSDEntry 1 }

vdslLineMCMConfProfileMaxRxPSDTone OBJECT-TYPE

SYNTAX Unsigned32 (1..4096)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The tone index for which the PSD is being specified.
 There must not be multiple rows defined, for a particular
 profile, with the same value for this field."

REFERENCE "T1E1.4/2000-013R4" -- Part 3, MCM

::= { vdslLineMCMConfProfileMaxRxPSDEntry 2 }

vdslLineMCMConfProfileMaxRxPSDPSD OBJECT-TYPE

SYNTAX Unsigned32

UNITS "0.5dBm/Hz"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Power Spectral Density level in steps of 0.5dBm/Hz with
 an offset of -140dBm/Hz."

REFERENCE "T1E1.4/2000-013R4" -- Part 3, MCM

::= { vdslLineMCMConfProfileMaxRxPSDEntry 3 }

vdslLineMCMConfProfileMaxRxPSDRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object is used to create a new row or modify or
 delete an existing row in this table."

A profile is activated by setting this object to 'active'.
 When 'active' is set, the system will validate the profile.
 There must be only one entry in this table for each tone
 associated with a specific profile. This will be checked
 during the validation process.

None of the columns in this row may be modified while the
 row is in the 'active' state.

Before a profile can be deleted or taken out of
 service, (by setting this object to 'destroy' or
 'notInService') it must be first unreferenced
 from all associated lines."

::= { vdslLineMCMConfProfileMaxRxPSDEntry 4 }

```

-- conformance information

vdsLineExtMCMConformance OBJECT IDENTIFIER ::=
    { vdsLineExtMCMmib 2 }
vdsLineExtMCMGroups OBJECT IDENTIFIER ::=
    { vdsLineExtMCMConformance 1 }
vdsLineExtMCMCompliances OBJECT IDENTIFIER ::=
    { vdsLineExtMCMConformance 2 }

vdsLineExtMCMmibCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for SNMP entities which
        manage VDSL interfaces."
    MODULE -- this module
    MANDATORY-GROUPS
    {
        vdsLineExtMCMGroup
    }

    ::= { vdsLineExtMCMCompliances 1 }

-- units of conformance

vdsLineExtMCMGroup OBJECT-GROUP
    OBJECTS
    {
        vdsLineMCMConfProfileTxWindowLength,
        vdsLineMCMConfProfileRowStatus,
        vdsLineMCMConfProfileTxBandStart,
        vdsLineMCMConfProfileTxBandStop,
        vdsLineMCMConfProfileTxBandRowStatus,
        vdsLineMCMConfProfileRxBandStart,
        vdsLineMCMConfProfileRxBandStop,
        vdsLineMCMConfProfileRxBandRowStatus,
        vdsLineMCMConfProfileTxPSDTone,
        vdsLineMCMConfProfileTxPSDPSD,
        vdsLineMCMConfProfileTxPSDRowStatus,
        vdsLineMCMConfProfileMaxTxPSDTone,
        vdsLineMCMConfProfileMaxTxPSDPSD,
        vdsLineMCMConfProfileMaxTxPSDRowStatus,
        vdsLineMCMConfProfileMaxRxPSDTone,
        vdsLineMCMConfProfileMaxRxPSDPSD,
        vdsLineMCMConfProfileMaxRxPSDRowStatus
    }
    STATUS current
    DESCRIPTION
        "A collection of objects providing configuration

```

```

        information for a VDSL line based upon multiple
        carrier modulation modem."
 ::= { vdslLineExtMCMGroups 1 }

```

END

5. Acknowledgments

This document contains many definitions taken from an early version of the VDSL MIB [RFC3728]. As such any credit for the text found within should be fully attributed to the authors of that document.

6. Security Considerations

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

```

vdslLineMCMConfProfileTable,
vdslLineMCMConfProfileTxWindowLength,
vdslLineMCMConfProfileRowStatus,
vdslLineMCMConfProfileTxBandTable,
vdslLineMCMConfProfileTxBandStart,
vdslLineMCMConfProfileTxBandStop,
vdslLineMCMConfProfileTxBandRowStatus,
vdslLineMCMConfProfileRxBandTable,
vdslLineMCMConfProfileRxBandStart,
vdslLineMCMConfProfileRxBandStop,
vdslLineMCMConfProfileRxBandRowStatus,
vdslLineMCMConfProfileTxPSDTable,
vdslLineMCMConfProfileTxPSDTone,
vdslLineMCMConfProfileTxPSDPSD,
vdslLineMCMConfProfileTxPSDRowStatus,
vdslLineMCMConfProfileMaxTxPSDTable,
vdslLineMCMConfProfileMaxTxPSDTone,
vdslLineMCMConfProfileMaxTxPSDPSD,
vdslLineMCMConfProfileMaxTxPSDRowStatus,
vdslLineMCMConfProfileMaxRxPSDTable,
vdslLineMCMConfProfileMaxRxPSDTone,
vdslLineMCMConfProfileMaxRxPSDPSD,
vdslLineMCMConfProfileMaxRxPSDRowStatus

```

VDSL layer connectivity from the Vtur will permit the subscriber to manipulate both the VDSL link directly and the VDSL embedded operations channel (EOC) for their own loop. For example, unchecked or unfiltered fluctuations initiated by the subscriber could generate sufficient notifications to potentially overwhelm either the management interface to the network or the element manager.

Additionally, allowing write access to configuration data may allow an end-user to increase their service levels or affect other end-users in either a positive or negative manner. For this reason, the tables and objects listed above should be considered to contain sensitive information.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

```
vdslLineMCMConfProfileTable,
vdslLineMCMConfProfileTxWindowLength,
vdslLineMCMConfProfileRowStatus,
vdslLineMCMConfProfileTxBandTable,
vdslLineMCMConfProfileTxBandStart,
vdslLineMCMConfProfileTxBandStop,
vdslLineMCMConfProfileTxBandRowStatus,
vdslLineMCMConfProfileRxBandTable,
vdslLineMCMConfProfileRxBandStart,
vdslLineMCMConfProfileRxBandStop,
vdslLineMCMConfProfileRxBandRowStatus,
vdslLineMCMConfProfileTxPSDTable,
vdslLineMCMConfProfileTxPSDTone,
vdslLineMCMConfProfileTxPSDPSD,
vdslLineMCMConfProfileTxPSDRowStatus,
vdslLineMCMConfProfileMaxTxPSDTable
vdslLineMCMConfProfileMaxTxPSDTone,
vdslLineMCMConfProfileMaxTxPSDPSD,
vdslLineMCMConfProfileMaxTxPSDRowStatus,
vdslLineMCMConfProfileMaxRxPSDTable
vdslLineMCMConfProfileMaxRxPSDTone,
vdslLineMCMConfProfileMaxRxPSDPSD,
vdslLineMCMConfProfileMaxRxPSDRowStatus
```

Read access of the physical band parameters may provide knowledge to an end-user that would allow malicious behavior, for example the application of an intentional interference on one or all of the physical bands in use.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of a MIB module which utilizes the textual conventions defined in this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

7. IANA Considerations

The IANA has assigned the transmission value 229 to VDSL-LINE-EXT-MCM-MIB.

8. References

8.1. Normative References

- [DSLFT57] DSL Forum TR-057, "VDSL Network Element Management", February 2003.
- [ETSI2701] ETSI TS 101 270-1 V1.2.1, "Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very high speed Digital Subscriber Line (VDSL); Part 1: Functional requirements", October 1999.
- [ETSI2702] ETSI TS 101 270-2 V1.1.1, "Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very high speed Digital Subscriber Line (VDSL); Part 1: Transceiver specification", February 2001.

- [ITU9931] ITU-T G.993.1, "Very-high-speed digital subscriber line foundation", November 2001.
- [ITU9971] ITU-T G.997.1, "Physical layer management for Digital Subscriber Line (DSL) Transceivers", July 1999.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, June 2000.
- [RFC3728] Ray, B. and R. Abbi, "Definitions of Managed Objects for Very High Speed Digital Subscriber Lines (VDSL)", RFC 3728, February 2004.
- [TlE1311] ANSI TlE1.4/2001-311, "Very-high-bit-rate Digital Subscriber Line (VDSL) Metallic Interface, Part 1: Functional Requirements and Common Specification", February 2001.
- [TlE1011] ANSI TlE1.4/2001-011R3, "VDSL Metallic Interface, Part 2: Technical Specification for a Single-Carrier Modulation (SCM) Transceiver", November 2001.
- [TlE1013] ANSI TlE1.4/2001-013R4, "VDSL Metallic Interface, Part 3: Technical Specification for a Multi-Carrier Modulation (MCM) Transceiver", November 2000.

8.2. Informative References

- [RFC3415] Wijnen, B., Presuhn, R., and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", STD 62, RFC 3415, December 2002.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart,
"Introduction and Applicability Statements for Internet-
Standard Management Framework", RFC 3410, December 2002.

Authors' Addresses

Menachem Dodge
ECI Telecom Ltd.
30 Hasivim St.
Petach Tikva 49517,
Israel

Phone: +972 3 926 8421
Fax: +972 3 928 7342
EMail: mbdodge@ieee.org

Bob Ray
PESA Switching Systems, Inc.
330-A Wynn Drive
Huntsville, AL 35805
USA

Phone: +1 256 726 9200 ext. 142
Fax: +1 256 726 9271
EMail: rray@pesa.com

Full Copyright Statement

Copyright (C) The Internet Society (2005).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

