

RSVP over ATM Implementation Guidelines

Status of this Memo

This document specifies an Internet Best Current Practices for the Internet Community, and requests discussion and suggestions for improvements. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (1998). All Rights Reserved.

Abstract

This memo presents specific implementation guidelines for running RSVP over ATM switched virtual circuits (SVCs). The general problem is discussed in [6]. Implementation requirements are discussed in [2]. Integrated Services to ATM service mappings are covered in [3]. The full set of documents present the background and information needed to implement Integrated Services and RSVP over ATM.

1. Introduction

This memo discusses running IP over ATM in an environment where SVCs are used to support QoS flows and RSVP is used as the internet level QoS signaling protocol. It applies when using CLIP/ION, LANE2.0 and MPOA methods for supporting IP over ATM. The general issues related to running RSVP[4] over ATM have been covered in several papers including [6] and other earlier work. This document is intended as a companion to [6,2] and as a guide to implementers. The reader should be familiar with both documents.

This document provides a recommended set of functionality for implementations using ATM UNI3.x and 4.0, while allowing for more sophisticated approaches. We expect some vendors to additionally provide some of the more sophisticated approaches described in [6], and some networks to only make use of such approaches. The recommended set of functionality is defined to ensure predictability and interoperability between different implementations. Requirements for RSVP over ATM implementations are provided in [2].

This document uses the same terms and assumption stated in [2]. Additionally, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [5].

2. Implementation Recommendations

This section provides implementation guidelines for implementation of RSVP over ATM. Several recommendations are common for all, RSVP sessions, both unicast and multicast. There are also recommendations that are unique to unicast and multicast session types.

2.1 RSVP Message VC Usage

The general issues related to which VC should be used for RSVP messages is covered in [6]. It discussed several implementation options including: mixed control and data, single control VC per session, single control VC multiplexed among sessions, and multiple VCs multiplexed among sessions. QoS for control VCs was also discussed. The general discussion is not repeated here and [6] should be reviewed for detailed information.

RSVP over ATM implementations SHOULD send RSVP control (messages) over the best effort data path, see figure 1. It is permissible to allow a user to override this behavior. The stated approach minimizes VC requirements since the best effort data path will need to exist in order for RSVP sessions to be established and in order for RSVP reservations to be initiated. The specific best effort paths that will be used by RSVP are: for unicast, the same VC used to reach the unicast destination; and for multicast, the same VC that is used for best effort traffic destined to the IP multicast group. Note that for multicast there may be another best effort VC that is used to carry session data traffic, i.e., for data that is both in the multicast group and matching a sessions protocol and port.




Figure 1: RSVP Control Message VC Usage

The disadvantage of this approach is that best effort VCs may not provide the reliability that RSVP needs. However the best effort path is expected to satisfy RSVP reliability requirements in most networks. Especially since RSVP allows for a certain amount of packet loss without any loss of state synchronization.

2.2 Aggregation

As discussed in [6], data associated with multiple RSVP sessions can be sent using the same shared VCs. Implementation of such "aggregation" models is still a matter for research. Therefore, RSVP over ATM implementations SHOULD use independent VCs for each RSVP reservation.

2.3 Short-Cuts

Short-cuts allow ATM attached routers and hosts to directly establish point-to-point VCs across LIS boundaries, i.e., the VC end-points are on different IP subnets. Short-cut support for unicast traffic has been defined in [7] and [1]. The ability for short-cuts and RSVP to interoperate has been raised as a general question. The area of concern is the ability to handle asymmetric short-cuts. Specifically how RSVP can handle the case where a downstream short-cut may not have a matching upstream short-cut. In this case, which is shown in figure 2, PATH and RESV messages following different paths.




Figure 2: Asymmetric RSVP Message Forwarding With ATM Short-Cuts

Examination of RSVP shows that the protocol already includes mechanisms that allows support of the asymmetric paths. The mechanism is the same one used to support RESV messages arriving at the wrong router and the wrong interface. RSVP messages are only processed when they arrive at the proper interface. When messages arrive on the wrong interface, they are forwarded by RSVP. The proper interface is indicated in the NHOP object of the message. So, existing RSVP mechanisms will support the asymmetric paths that can occur when using short-cuts.

The short-cut model of VC establishment still poses several issues when running with RSVP. The major issues are dealing with established best effort short-cuts, when to establish short-cuts, and QoS only short-cuts. These issues will need to be addressed by RSVP implementations.

The key issue to be addressed by RSVP over ATM implementations is when to establish a short-cut for a QoS data flow. RSVP over ATM implementations SHOULD simply follow best effort traffic. When a short-cut has been established for best effort traffic to a destination or next-hop, that same end-point SHOULD be used when setting up RSVP triggered VCs for QoS traffic to the same destination or next-hop. This will happen naturally when PATH messages are forwarded over the best effort short-cut. Note that in this

Since there is not one model that satisfies all cases, implementations SHOULD implement one of either the limited heterogeneity model or the modified homogeneous model. Implementations SHOULD support both approaches and provide the ability to select which method is actually used, but are not required to do so.

3. Security Considerations

The same considerations stated in [4] and [8] apply to this document. There are no additional security issues raised in this document.

4. Acknowledgments

This work is based on earlier drafts and comments from the ISSLL working group. The author would like to acknowledge their contribution, most notably Steve Berson who coauthored one of the drafts.

5. Author's Address

Lou Berger
FORE Systems
1595 Spring Hill Road
5th Floor
Vienna, VA 22182

Phone: +1 703-245-4527
EMail: lberger@fore.com

REFERENCES

- [1] The ATM Forum, "MPOA Baseline Version 1", May 1997.
- [2] Berger, L., "RSVP over ATM Implementation Requirements", RFC 2380, August 1998.
- [3] Borden, M., and M. Garrett, "Interoperation of Controlled-Load and Guaranteed-Service with ATM", RFC 2381, August 1998.
- [4] Braden, R., Zhang, L., Berson, S., Herzog, S., and S. Jamin, "Resource ReSerVation Protocol (RSVP) -- Version 1 Functional Specification", RFC 2205, September 1997.
- [5] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [6] Crawley, E., Berger, L., Berson, S., Baker, F., Borden, M., and J. Krawczyk, "A Framework for Integrated Services and RSVP over ATM", RFC 2382, August 1998.
- [7] Luciani, J., Katz, D., Piscitello, D., and B. Cole, "NBMA Next Hop Resolution Protocol (NHRP)", RFC 2332, April 1998.
- [8] Perez, M., Liaw, F., Grossman, D., Mankin, A., Hoffman, E., and A. Malis, "ATM Signalling Support for IP over ATM", RFC 1755, February 1995.

Full Copyright Statement

Copyright (C) The Internet Society (1998). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

