

## Sieve Email Filtering -- Subaddress Extension

### Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

### Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

### Abstract

On email systems that allow for "subaddressing" or "detailed addressing" (e.g., "ken+sieve@example.org"), it is sometimes desirable to make comparisons against these sub-parts of addresses. This document defines an extension to the Sieve mail filtering language that allows users to compare against the user and detail parts of an address.

### Table of Contents

1. Introduction. . . . .	2
2. Capability Identifier . . . . .	2
3. Subaddress Comparisons. . . . .	2
4. Security Considerations . . . . .	4
5. IANA Considerations . . . . .	4
6. Normative References. . . . .	4
7. Acknowledgments . . . . .	5
8. Intellectual Property Statement . . . . .	5
9. Author's Address. . . . .	5
10. Full Copyright Statement. . . . .	6

## 1. Introduction

Subaddressing is the practice of appending some "detail" information to the local-part of an [IMAIL] address to indicate that the message should be delivered to the mailbox specified by the "detail" information. The "detail" information is prefixed with a special "separator character" (typically "+") which forms the boundary between the "user" (original local-part) and the "detail" sub-parts of the address, much like the "@" character forms the boundary between the local-part and domain.

Typical uses of subaddressing might be:

- A message addressed to "ken+sieve@example.org" is delivered into a mailbox called "sieve" belonging to the user "ken".
- A message addressed to "5551212#123@example.org" is delivered to the voice mailbox number "123" at phone number "5551212".

This document describes an extension to the Sieve language defined by [SIEVE] for comparing against the "user" and "detail" sub-parts of an address.

Conventions for notations are as in [SIEVE] section 1.1, including use of [KEYWORDS].

## 2. Capability Identifier

The capability string associated with the extension defined in this document is "subaddress".

## 3. Subaddress Comparisons

Commands that act exclusively on addresses may take the optional tagged arguments ":user" and ":detail" to specify what sub-part of the local-part of the address will be acted upon.

NOTE: In most cases, the envelope "to" address is the preferred address to examine for subaddress information when the desire is to sort messages based on how they were addressed so as to get to a specific recipient. The envelope address is, after all, the reason a given message is being processed by a given sieve script for a given user. This is particularly true when mailing lists, aliases, and "virtual domains" are involved since the envelope may be the only source of detail information for the specific recipient.

The `":user"` argument specifies that sub-part of the local-part which lies to the left of the separator character (e.g., "ken" in "ken+sieve@example.org"). If no separator character exists, then `":user"` specifies the entire left-side of the address (equivalent to `":localpart"`).

The `":detail"` argument specifies that sub-part of the local-part which lies to the right of the separator character (e.g., "sieve" in "ken+sieve@example.org"). If no separator character exists, the test evaluates to false. If nothing lies to the right of the separator character, then `":detail"` `":is"` the null key (`"`). Otherwise, the `":detail"` sub-part contains the null key.

Implementations MUST make sure that the separator character matches that which is used and/or allowed by the encompassing mail system, otherwise unexpected results might occur. Implementations SHOULD allow the separator character to be configurable so that they may be used with a variety of mail systems. Note that the mechanisms used to define and/or query the separator character used by the mail system are outside the scope of this document.

The `":user"` and `":detail"` address parts are subject to the same rules and restrictions as the standard address parts defined in [SIEVE]. For convenience, the "ADDRESS-PART" syntax element defined in [SIEVE] is augmented here as follows:

```
ADDRESS-PART  =/  ":user" / ":detail"
```

A diagram showing the ADDRESS-PARTs of a email address utilizing a separator character of '+' is shown below:

```
      :user "+" :detail  "@" :domain
      \-----/
      :local-part
```

Example:

```
require "subaddress";
```

```
# File mailing list messages (subscribed as "ken+mta-filters").
if envelope :detail "to" "mta-filters" {
    fileinto "inbox.ietf-mta-filters";
}
```

```
# If a message is not to me (ignoring +detail), junk it.
if not allof (address :user ["to", "cc", "bcc"] "ken",
    address :domain ["to", "cc", "bcc"] "example.org") {
    discard;
```

```
}  
  
# Redirect all mail sent to +foo.  
if envelope :detail ["to", "cc", "bcc"] "foo" {  
    redirect "ken@example.edu";  
}
```

#### 4. Security Considerations

Security considerations are discussed in [SIEVE]. It is believed that this extension does not introduce any additional security concerns.

#### 5. IANA Considerations

The following template specifies the IANA registration of the Sieve extension specified in this document:

To: iana@iana.org  
Subject: Registration of new Sieve extension

Capability name: subaddress  
Capability keyword: subaddress  
Capability arguments: N/A  
Standards Track/RFC 3598  
Person and email address to contact for further information:

Kenneth Murchison  
ken@oceana.com

This information has been added to the list of sieve extensions given on <http://www.iana.org/assignments/sieve-extensions>.

#### 6. Normative References

- [IMAIL] Resnick, P., Ed., "Internet Message Format", RFC 2822, April 2001.
- [KEYWORDS] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [SIEVE] Showalter, T., "Sieve: A Mail Filtering Language", RFC 3028, January 2001.

## 7. Acknowledgments

Thanks to Tim Showalter, Alexey Melnikov, Michael Salmon, Randall Gellens, Philip Guenther and Jutta Degener for their help with this document.

## 8. Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

## 9. Author's Address

Kenneth Murchison  
Oceana Matrix Ltd.  
21 Princeton Place  
Orchard Park, NY 14127

EMail: ken@oceana.com

## 10. Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assignees.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

